

**NOT RECOMMENDED FOR NEW DESIGNS!**  
(LAST TIME BUY: 30<sup>th</sup> Oct 2020)

**RECOM**  
AC/DC Converter

## Features

- Universal AC input (85-264VAC)
- Protections: SCP, OVP, OLP, OTP
- DC OK indicator LED with relay contacts
- 150% (360W) peak load capacity
- Built-in active PFC, PF>0.95
- High efficiency up to 94%

## DIN Rail Series

## REDIN240

## 240 Watt DIN-Rail Power Supply



### Description

These DIN-rail mounted power supplies have a robust case, 4mm screw terminal connectors and use high reliability components to give a long, trouble-free life. The REDIN240 can be end mounted to save rail space or side mounted for use in low-profile cabinets. The units can deliver up to 150% start-up power and allow n+1 parallel operation to increase the continuous output current or for supply redundancy. Relay contacts simplify DC OK monitoring. The REDIN240 series is designed for demanding commercial and industrial applications with UL508, UL60950, IEC60950 CB report and CE (LVD + EMC + RoHS) certifications. They come with a full 5-year warranty.

### Selection Guide

Part Number	nom. Input Voltage Range [VAC]	Output Voltage [VDC]	Output Adjustability [VDC]	Rated Current [A]	Efficiency typ. [%]
REDIN240-24	100-240	24	24-28	10	94.35
REDIN240-48	100-240	48	48-56	5	93.7

### Specifications (measured @ Ta = 25°C, rated Vin, rated load and after warm up)

BASIC CHARACTERISTICS					
Parameter	Condition		Min.	Typ.	Max.
Input Voltage Range			85VAC		264VAC
Absolute Maximum Input Voltage	max. 3 seconds				300VAC 375VDC
Input Current	full load, 115VAC full load, 230VAC			2.28A 1.13A	3.0A 1.5A
Inrush Current	cold start at 25°C, 115VAC cold start at 25°C, 230VAC			15A 32A	20A 40A
No Load Power Consumption	85-264VAC 230VAC			2.2W 1.8W	4W 3W
Input Frequency Range			47Hz		63Hz
Output Trim	24Vout 48Vout		24V 48V		28V 56V
Power Factor	115VAC 230VAC			0.99 0.95	
Start-up time	24Vout	115VAC 230VAC		1.48s 1.27s	3s
	48Vout	115VAC 230VAC		1.45s 1.25s	
Hold-up time	24Vout	230VAC	20ms	26.28ms	
	48Vout		20ms	24.74ms	
Rise time	24Vout	230VAC		16.62ms	100ms
	48Vout			26.27ms	
Ripple & Noise <sup>(1)</sup>	0 - 70°C -25°C	24Vout			240mVp-p 480mVp-p
	-25 - 70°C	48Vout			480mVp-p

**Notes:**  
Note1: Measured at 20MHz bandwidth by using a 12" twisted pair-wire terminated with a 0.1µF & 10µF parallel capacitor

continued on next page




UL60950-1 certified  
UL508 certified  
IEC/EN60950-1 certified  
EN55022/24 compliant


Specifications (measured @ Ta = 25°C, rated Vin, rated load and after warm up)

### REDIN240-24


Efficiency vs. Load




Power Dissipation vs Load



Input Current vs Load




Power Factor vs Load over Vin




### REDIN240-48

Efficiency vs. Load




Power Dissipation vs Load




**Specifications** (measured @ Ta = 25°C, rated Vin, rated load and after warm up)

**REDIN240-48**

**Input Current vs Load**



**Power Factor vs Load over Vin**



**REGULATION**

Parameter	Condition	Value
Output Accuracy	24Vout	±0.4% typ. / ±3% max.
	48Vout	±0.3% typ. / ±3% max.
Line Regulation	24Vout	±0.03% typ. / ±0.5% max.
	48Vout	±0.04% typ. / ±0.5% max.
Load Regulation	0% to 100% load	0.3% typ. / 1.0% max.
Transient Response	100Hz & 1kHz, 50% duty, 25% load step change	±1% typ. / ±5% max.

**PROTECTION**

Parameter	Condition	Value
Input Fuse <sup>(2)</sup>		T5A, slow blow type
Short Circuit Protection (SCP)		continuous, auto recovery
Over Voltage Protection (OVP)	24Vout	29-33VDC, constant voltage auto recovery
	48Vout	58-63VDC, constant voltage auto recovery
Over Voltage Category (OVC)		OVC II
Over Load Protection (OLP)		Limit the current by constant power circuit
Over Temperature Protection (OTP)		105±5°C, detect on Heat-sink of power transistor; shut down O/P, auto recovery after temperature goes down
Isolation Voltage	I/P to O/P	3.0kVAC/1 minute
	I/P to PE	2.5kVAC/1 minute
	O/P to PE	0.5kVAC/1 minute
Isolation Resistance		10MΩ min.
Leakage Current	I/P to O/P	0.25mA max.
	I/P to PE	3.5mA max.
Power OK LED	ON	Vout up to 90% of rated Vout
	OFF	Vout down to 80% of rated Vout
Relay Contact Rating		Max. 30V/1A or 60V/0.3 or 30VAC/0.3A Resistive Load


continued on next page

**Specifications** (measured @ Ta = 25°C, rated Vin, rated load and after warm up)

**Notes:**

Note2: Refer to local safety regulations if input over-current protection is also required


**Overload Capability**




**ENVIRONMENTAL**

Parameter	Condition	Value
Operating Temperature Range	@ natural convection 0.1m/s	full load -25°C to +50°C
		refer to derating graph -25°C to +70°C
Temperature Coefficient		0.3%/K
Operating Altitude		3000m
Operating Humidity	non-condensing	20% - 90% RH
IP Rating		IP X0
Pollution Degree (PD)		PD 2
Shock		10-500Hz 2G, 60min.
Vibration		10G /11 ms, along x,y and z axis
MTBF	according to MIL-HDBK-217F, 25°C	300 x 10 <sup>3</sup> hours

**Thermal Dertating**



**Operating Altitude**



**Specifications** (measured @ Ta = 25°C, rated Vin, rated load and after warm up)
**Notes:**

- Note3: UL Report certified temperature range: -25°C to +50°C. According to RECOM internal qualification the device is rated up to +70°C with derating
- Note4: UL Report certified operating altitude: 5000m. According to RECOM internal qualification the device is rated up to 3000m. For altitude higher than 2000m, derating 30W for every 1000m, or 5°C/1000m

**SAFETY AND CERTIFICATIONS**

Certificate Type	Report / File Number	Standard
Information Technology Equipment, General Requirements for Safety	E224736	UL60950-1, 2nd Edition, 2014 CSA C22.2 No. 60950-1-07, 2nd Edition, 2014
Industrial Control Equipment	E470721	UL508, 17th Edition, 2013 CSA C22.2 No. 107.1-01, 3rd Edition, 2011
Information Technology Equipment - General Requirements for Safety	NTEK-2016NT02244417S	IEC60950-1, 2nd Edition 2005, + AM2:2013 EN60950-1:2006, + A2:2013
EAC	RU-AT.37.02367	TP TC 004/2011
RoHS2+		RoHS 2011/65/EU

EMC Compliance	Report / Condition	Standard / Criterion
Information technology equipment - Radio disturbance characteristics - Limits and methods of measurement		EN55022:2010 + AC:2011, Class B
Information technology equipment - Immunity characteristics - Limits and methods of measurement		EN55024:2010 + A1:2015
Limitations on the amount of electromagnetic interference allowed from digital and electronic devices		47 CFR FCC Part 15, Subpart B: 2016
ESD Electrostatic discharge immunity test	Air ±8kV, Contact ±4kV	EN61000-4-2, 2009, Criteria B
Radiated, radio-frequency, electromagnetic field immunity test	3V/m	EN61000-4-3, 2006, Criteria A
Fast Transient and Burst Immunity	AC Power Port: L+N+PE ±1kV	EN61000-4-4, 2012, Criteria B
Surge Immunity	AC Power Port L-N ±1kV, L-PE + N-PE ±2kV	EN61000-4-5, 2014, Criteria B
Immunity to conducted disturbances, induced by radio-frequency fields	AC Power Port 3V	EN61000-4-6, 2014, Criteria A
Power Magnetic Field Immunity	50Hz, 1A/m	EN61000-4-8, 2010, Criteria A
Voltage Dips and Interruptions	Voltage Dips >95% Voltage Dips 30% Voltage Interruptions >95%	EN61000-4-11, 2004, Criteria B EN61000-4-11, 2004, Criteria C EN61000-4-11, 2004, Criteria C
Limits of Harmonic Current Emissions		EN61000-3-2, 2014, Criteria A
Voltage Fluctuations & Flicker		EN61000-3-3, 2013, Clause 5



**DIMENSION and PHYSICAL CHARACTERISTICS**

Parameter	Type	Value
Material	case	aluminium
	cover	nickel plated steel
Dimension (LxWxH)	without mounting clip	114.26 x 46.0 x 124.4mm
Weight		810g typ.

continued on next page

**Specifications** (measured @ Ta = 25°C, rated Vin, rated load and after warm up)

Dimension Drawing (mm)




Terminals and Wiring	
Type	Screw Connector
Solid Wire	1-6mm <sup>2</sup>
Stranded Wire	1-4mm <sup>2</sup>
American Wire Gauge	AWG17-10
Wire Stripping Length	8mm
Screwdriver (slotted / cross)	3.5mm
Recommended tightening torque	0.5Nm-0.8Nm
Tolerance: X.X ±0.5mm X.XX ±0.25mm	

Specifications (measured @ Ta = 25°C, rated Vin, rated load and after warm up)


### INSTALLATION

#### Mounting Instruction




### INSTALLATION

#### Mounting Multiple Power Supplies



**Specifications** (measured @ Ta = 25°C, rated Vin, rated load and after warm up)

**Parallel Operation & Phase Redundancy**



**Single Operation:**

- 1) Make sure that the front panel switch is set to "single Use".
- 2) The output voltage can be increased by trim pot to compensate any cable losses.


**Parallel Operation:**

- 1) Make sure that the front panel switch is set to "single Use" on each power supply.
- 2) Adjust each power supply to the exact same output voltage with same load and cooling conditions.
- 3) Set the front panel switches to "Parallel Use." Use the same wire length for each power supply (star connection) and energize all units at the same time to avoid triggering overload protection.

Derate the maximum output power to 90% of nominal ratings.

For operation with more than three power supplies in parallel or series operation, please contact RECOM technical support for advice.

**BLOCK DIAGRAMM**



**PACKAGING INFORMATION**

Parameter	Type	Value
Packaging Dimension (LxWxH)	cardboard box	140.0 x 63.0 x 142.0mm
Packaging Quantity	cardboard box	1pcs
Storage Temperature Range		-40°C to +85°C
Storage Humidity		5% - 95% RH

The product information and specifications may be subject to changes even without prior written notice. The product has been designed for various applications; its suitability lies in the responsibility of each customer. The products are not authorized for use in safety-critical applications without RECOM's explicit written consent. A safety-critical application is an application where a failure may reasonably be expected to endanger or cause loss of life, inflict bodily harm or damage property. The applicant shall indemnify and hold harmless RECOM, its affiliated companies and its representatives against any damage claims in connection with the unauthorized use of RECOM products in such safety-critical applications.