

RAC03-C Series

Specifications (measured at Ta= 25°C, full load otherwise noted)

DIMENSION AND PHYSICAL CHARACTERISTIC	S	
Parameter	Туре	Value
	case	black plattic (UL94V-C
Material	potting	silicon VL94V-C
Dimension (LxWxH)		37.8 x 23.0 4mr
Weight		30g
Dimension Drawing (mm) 37.8	Recomme Footprint De. restricted as for PCB layout	Pin Connections Pin # Single 1 VAC in (L) 3 VAC in (N) 13 NC 14 -Vout 16 +Vout NC= no connection Tolerance: xx.x= ±0.5mm

PACKAGING INFO		
Parameter	Туре	Value
Packaging Dimel n (LxWxH)	tube	520.0 x 32.0 x 27.0mm
Packer		12pcs
Sto ge Tempe ve Range		-40°C to +100°C
S. re Humidity	non-condensing	95% RH max.

The product information and specifications may be subject to changes even without prior written notice. The product has been designed for various applications; its suitability lies in the responsibility of each customer. The products are not authorized for use in safety-critical applications without RECOM's explicit written consent. A safety-critical application is an application where a failure may reasonably be expected to endanger or cause loss of life, inflict bodily harm or damage property. The applicant shall indemnify and hold harmless RECOM, its affiliated companies and its representatives against any damage claims in connection with the unauthorized use of RECOM products in such safety-critical applications.

www.recom-power.com REV.: 2/2019 PA-5